




Since : 1990




Extruder Duty Helical Gear Box



 YouTube Video

Gear Box Internal Composition



- **Gear Case**

Super Rigid Housing of
Graded Cast Iron Machine on
High - Precision Machine

- **Output Hollow Shaft**

Made From High Graded Alloy Steel
Harden & Ground

- **Bearing**

Top quality Roller bearings
to be selected precisely calculated
for carry heavy load

- **Water Cooling**

In-built


- **Gears**

Made From High Graded Alloy Steel
Harden (HRC - 58 to 61) and Precision
Profile Ground to Meet Higher Standard
DIN 5 / DIN 6

- **Oil Seal**

Input / Output Shafts Incorporate
Double Oil Seals Imported

- **Assembly**



Gears and housing are assembled
and test-run by technicians
after stringent QC.

Bearing temperature is 100% tested
During the trial operation.

Noise is kept below the standard 90dB.

Recommend Lubricant

Synthetic Oil

ISO VG 320

100% PAO (Poly Alfa Olefins)


Base Synthetic Oil

- Up to 4 times longer oil life compared to any conventional mineral oil.
- Deliver energy efficiency.
- Observe temperature reduction.
- Increased gear & bearing life.
- Lesser evaporation due to lower velocity

Mineral Oil

ISO VG 320 / 460

Changing Period : 6000 Hours



INPUT SHAFT

TYPE	GEARBOX HOUSING DIMENSION															
MODEL	C	C1	C2	A	H	h	Z	T	P	Q	B	F	L2	J1	J2	ØK
SBH-90	155	115	90	330	215	105	60	55	220	N/A	156	132	63	78	145	14
SBH-110	190	167	110	456	265	133	118	49	358	N/A	186	165	86	93	209	14
SBH-125	215	172	125	485	285	143	122	50	185	200	205	170	108	103	203	14
SBH-140	240	196	140	535	340	170	140	56	203	220	215	190	118	108	232	17
SBH-160	270	184	160	578	356	178	125	59	205	255	265	230	127	133	270	19
SBH-180	305	220	180	636	395	198	153	67	222	280	280	250	148	140	272	21
SBH-200	340	232	200	702	420	210	161	71	260	300	296	265	139	148	321	23
SBH-225	385	260	225	790	484	242	180	80	300	330	330	280	180	165	330	25
SBH-250	430	320	250	980	582	291	205	115	375	375	412	352	171	206	399	27





TYPE	INPUT SHAFT				MOUNTING FLANGE								THRUST	WEIGHT	OIL
MODEL	ØD1	L1	X1	Y1		ØM	ØN	Ø N1	W1	W2	Ø R	Ø S	(BRG)*	(APPROX)*	QUANTITY*
SBH-90	20	55	6	16.5		150	100	60	7	5	125	M10	32309	90Kg	4 Ltr
SBH-110	25	60	8	21		220	115	80	8	5	180	M12	29414	100Kg	5 Ltr
SBH-125	30	80	8	26		240	130	90	8	5	200	M12	29416	125Kg	7 Ltr
SBH-140	35	80	10	30		285	200	110	8	5	240	M12	29418	173Kg	10 Ltr
SBH-160	45	105	14	39.5		285	200	125	10	5	250	M16	29420	236Kg	15 Ltr
SBH-180	50	110	14	44.5		315	200	130	10	5	280	M16	29422	300Kg	20 Ltr
SBH-200	50	110	16	44		360	240	150	10	5	290	M20	29426	460Kg	30 Ltr
SBH-225	60	140	18	53		400	245	165	14	5	325	M24	29430	675Kg	50 Ltr
SBH-250	70	140	20	62.5		475	340	210	14	5	410	M24	29434	900Kg	70 Ltr

Note :

All Dimensions are in mm.

*Condition Apply

Available Ratio :- 6:1, 8:1, 10:1, 13:1, 15:1, 17:1, 20:1, 22:1.






(PLAST INDIA) 2018 Exhibition
Gandhinagar, Gjuarat






(PLAST INDIA) 2018 Exhibition
Gandhinagar, Gujarat



DETAILS OF HOLLOW SHAFT



SBH - 90			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 50mm*
Ø20	6.0	22.8	
Ø22	6.0	24.8	
Ø25	8.0	28.3	
Splines Available on Request**			

SBH - 110			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 75mm*
Ø25	8.0	28.3	
Ø30	8.0	33.3	
Ø35	10.0	38.3	
Splines Available on Request**			

SBH - 125			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 85mm*
Ø30	8.0	33.3	
Ø35	10.0	38.3	
Ø40	12.0	43.3	
Splines Available on Request**			

SBH - 140			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 100mm*
Ø40	12.0	43.3	
Ø45	14.0	48.8	
Ø50	14.0	53.8	
Splines Available on Request**			

SBH - 160			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 140mm*
Ø50	14.0	53.8	
Ø55	16.0	59.3	
Ø60	18.0	64.4	
Splines Available on Request**			

SBH - 180			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 150mm*
Ø60	18.0	64.4	
Ø65	18.0	69.4	
Ø70	20.0	74.9	
Splines Available on Request**			


SBH - 200			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 160mm*
Ø75	22.0	79.9	
Ø80	22.0	85.4	
Ø85	22.0	90.4	
Ø90	25.0	95.4	
Splines Available on Request**			

SBH - 225			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 175mm*
Ø80	22.0	85.4	
Ø85	22.0	90.4	
Ø90	25.0	95.4	
Ø100	28.0	108.4	
Splines Available on Request**			

SBH - 250			
Available Standard Bore & Keyway			
Output Shaft Dia. ØD2	Keyway X	Keyway Y	L = 200mm*
Ø80	22.0	87.0	
Ø90	25.0	97.0	
Ø100	28.0	108.0	
Ø110	32.0	119.0	
Ø120	32.0	129.0	
Splines Available on Request**			

Service & Maintenance

Extend the life of your Gearbox



with predictive maintenance.

J. S. Gears

Anyone deciding in favour of **J. S.** high-performance gear unit automatically decides in favour of state-of-the-art engineering, efficient order handling and proven workflows. The know-how gathered in the course of decades enables us to fulfil all our customers' special requirements in many different sectors – from plastics via food processing all the way to heavy industry and energy supply – flexibly and customized. **J. S.** provides comprehensive advice on selecting the right gearing solution, on dimensioning and on drafting technical specifications. Solid engineering competence goes with real effectiveness in implementing gearing solutions; this includes designing with innovative tools, planning production transparently and fabricating with ultra-modern equipment – adding up to your fastest and most productive path to your high-performance gear system from the experts.

Our Core Strength

- One contact principle
- Quality Assurance
- All-round professionals
- Sustain ability Guarantee

All-round professionals

We at **J. S.** rely on mutual appreciation, respect and loyalty in its relations with customers and employees alike. Apart from financial independence, sustainability is the foundation of our company.

Fast fix Guarantee

We guarantee that your gear system will be serviced / maintained / repaired as fast as possible. We fabricate all the replacement parts needed ourselves which provides the decisive advantage in speed and time.

Quality Assurance

We use exclusively materials and components of selected, consistent quality. External and in-house test guarantee the highest quality of gear system solutions.

One contact principle

At **J. S.** you talk to just one contact who will handle all your requests. He/she does not just supervise the entire service procedure but can also answer all your questions at any time.



Contact



E-Catalogue



Video


(An ISO 9001 : 2015 Certified Company)



51, Saundarya Industrial Park, Bakrol-Bujrang Village, Tal.: Daskroi, Dist.: AHMEDABAD-382 430. Gujarat, INDIA.

Landline ☎ : +91 98242 46063 📞 : +91 72111 28033

✉ : jsgears@jsgears.in 🌐 : www.jsgears.in

© All rights reserved. No part of this publication may be reproduced, stored in retrieval system, or transmitted any form or by any means, electronic, mechanical, photocopying, recording or otherwise without the prior written permission of the owner. Any breach will entail legal action and prosecution without further notice.